



@IHVWLDQHO/HVL
#PRELOOVL

Fast Recharge Plus

Komercialna EV polnilna postaja

Tehnične podrobnosti	TRIO 3 priključki	DUETTO 2 priključka
Izhodni priključki ¹	- CCS Combo2 50 kW max - CHAdeMO 50 kW max - Type 2 43 kW max @ 64 A ali Type 2 22 kW max @ 32 A	- CCS Combo2 50 kW max - Type 2 22 kW max @ 32 A
Izhodna napetost/ Tokovni nivoji	DC: Max 500 V / 120 A AC: Max 400 V / 63 A	DC: Max 500 V / 120 A AC: Max 400 V / 32 A
Dolžina kabla	4-5 m	4-5 m
Temperaturni razpon delovanja	-25° C to +50° C	-25° C to +50° C
Največja izhodna moč	93 kW	72 kW max
Vhodna AC napetost	400 VAC ± 10%, 50 Hz	400 VAC ± 10%, 50 Hz
Vhodna AC priključitev	3 P + N + PE	3 P + N + PE
Najvišji hrup pri polni obremenitvi	< 65 dB A	< 65 dB A
Zaščita IP	IP 55	IP 55
Učinkovitost ²	95%	95%
Faktor moči	> 0.97	> 0.97
Največja moč v mirovanju	< 50 W	< 50 W
RFID standardi branja	ISO/IEC 14443 Type A/B NFC reading mode	ISO/IEC 14443 Type A/B NFC reading mode
Merilna lestvica za pametno polnjenje	Down to 60 kW	Down to 60 kW
EV-EVSE komunikacijski protokol	CHAdeMO 1.0.1 DIN 70121 IEC 61851-1 2 nd ed.	DIN 70121 IEC 61851-1 2 nd ed.
Prikazovalnik	8" viden ob dnevni svetlobi zaslon na dotik	8" viden ob dnevni svetlobi zaslon na dotik
Dimenzije (G x Š x V)	0.5 x 1 x 1.8 m	0.5 x 1 x 1.8 m
Teža	500 kg	500 kg
Izbirna možnost	3D high-end ovitek za blagovno znamko	3D high-end ovitek za blagovno znamko

¹ CCS and CHAdeMO are mutually exclusive outputs; cannot be engaged simultaneously.

² Efficiency for DC charging is certified at maximum power output.

Compatible with all EV models available in the market. The product is compliant with EU Directive 94/2014.

1FR0323CEU-Hyy